



## 2.5YD STATIC COMPACTOR FOR HAND LOADING

Motor Rating	7.5	KW
Power Supply Rating	415	VOLT 3 PHASE 32 AMP
Control Panel Voltage	24	VOLT
Clear Aperture Width	1430	MM
Clear Aperture Length	1400	MM
Charge Box Depth	940	MM
Charge Box Volume	1.88	M <sup>3</sup>
CHEM Volume Per Stroke	1.60	M <sup>3</sup>
Cycle Time	45	SEC
CHEM Volume Per Hour	1.51	M <sup>3</sup>
Overall Height (Top of Flange)	1300	MM
Overall Length	4020	MM
Overall Width	1720	MM
Basic Hydraulic Pressure	150	BAR
Hydraulic Capacity	150	LITRES
Total Weight	2.8	TONNE



### 2.5YD STATIC COMPACTOR WITH BIN LIFTER

Motor Rating	7.5	KW
Power Supply Rating	415	VOLT 3 PHASE 32 AMP
Control Panel Voltage	24	VOLT
Clear Aperture Width	1430	MM
Clear Aperture Length	1400	MM
Charge Box Depth	940	MM
Charge Box Volume	1.88	M <sup>3</sup>
CHEM Volume Per Stroke	1.60	M <sup>3</sup>
Cycle Time	54	SEC
CHEM Volume Per Hour	1.51	M <sup>3</sup>
Overall Height (Excluding Hopper)	1300	MM
Overall Length	4020	MM
Overall Width (Excluding Cage)	2220	MM
Basic Hydraulic Pressure	150	BAR
Hydraulic Capacity	150	LITRES
Total Weight	3.4	TONNE

If the machine is fitted with a Side Loading Bin Lifter with standard End Entry Cage the overall width would be 4720mm.



### 4YD STATIC COMPACTOR FOR HAND LOADING

Motor Rating	11	KW
Power Supply Rating	415	VOLT 3 PHASE 45 AMP
Control Panel Voltage	24	VOLT
Clear Aperture Width	1500	MM
Clear Aperture Length	2200	MM
Charge Box Depth	940	MM
Press Force	38	TONNE
Cycle Time	60	SEC
Cylinder Bore	160	MM
Overall Height (Top of Flange)	1300	MM (not including hopper)
Overall Length	5175	MM
Overall Width	1880	MM
Basic Hydraulic Pressure	150	BAR
Ram Penetration	400	MM
Hydraulic Capacity	250	LITRES
Total Weight	3.9	TONNE